



JABO

SUPPLY CORPORATION

CABLE GUARD-
RUBBER PROTECTION

PVC CABLE GUARD

SPLIT AND NON SPLIT AVAILABLE



SPLIT GUARD SHOWN ABOVE

RUBBER CABLE PROTECTION HOSE



CABLE GUARDING/ RUBBER CABLE PROTECTION

JABO SUPPLY



5 LOCATIONS

PARKERSBURG, WV

10085 Emerson Avenue 26102
(304) 464-4400

MORGANFIELD, KY

118 Jim Veatch Road, 42437
(270) 389-3430

HUNTINGTON, WV

209 Braley Street, 25705
(304) 736-8333

NORTON, VA

205 Hawthorne Drive, 24273
(276) 679-1224


BEAVER, WV (BECKLEY)

227 C&O Shop Road 25813
(304-252-0000

SINCE 1964 SERVICE IS MORE THAN A PROMISE

CABLE GUARD SPLIT

CABLE GUARD

PRE-SPLIT		
		
JABO PART#	SIZE	WORKING PSI 68F/104F
*	1"	NA/NA
*	1-1/4"	NA/NA
*	1-1/2"	NA/NA
034-31940	2"	12/6
*	2-3/8"	12/6
*	2-1/2"	10/5
034-31950	3"	8/4
*	3-1/2"	8/4
*	4"	6/3
*Non Stock - Call Jabo Supply		
ABOVE # FOR PRE-SPLIT		
CALL JABO FOR NON SPLIT		



“Cover Guard” CG™/CG-SL™ Series

PVC Ducting and Cover Protection Hose

General Applications:

- Cable and hose bundle protection (MSHA)
- Dust collection
- Ducting, ventilation and fume removal
- Mine supply line cover protection

Construction: PVC tube with rigid PVC helix.

Service Temperature Range:

-4°F (-20°C) to +150°F (+65°C)*

- **MSHA⁽⁰⁸⁾ Approved** – Meets U.S. Dept. of Labor Administration requirements for flame-resistance for use in mines for protection of hose bundles. Optional, special order, red or green colored helix also approved.

AVAILABLE IN SPLIT AND PRE-SPLIT FROM THE FACTORY

Nominal Specifications

Series Number	ID		OD		Working Pressure (psi)		Vacuum Rating Hg (in)		Min. Bending Radius at 68°F (in)	Standard Length (ft)	Weight (lbs/ft)
	(in)	(mm)	(in)	(mm)	68°F	104°F	68°F	104°F			
CG-SL100	1	25.4	1.28	31.9	n/a	n/a	n/a	n/a	.5	100	0.14
CG-SL125	1-1/4	31.8	1.51	38.4	n/a	n/a	n/a	n/a	.75	100	0.18
CG-SL150	1-1/2	38.1	1.76	45.1	n/a	n/a	n/a	n/a	1	100	0.21
CG/CG-SL200	2	50.8	2.30	58.4	12	6	10	5	2	100	0.28
CG238	2-3/8	60.3	2.76	70.1	12	6	10	5	2	100	0.38
CG/CG-SL250	2-1/2	63.5	2.81	71.3	10	5	8	4	2	100	0.39
CG/CG-SL300	3	76.2	3.35	85.0	8	4	7	3	3	100	0.45
CG/CG-SL350	3-1/2	88.9	3.83	97.4	8	4	7	3	3	100	0.51
CG/CG-SL400	4	102.4	4.39	111.4	6	3	6	3	3	100	0.64

RUBBER CABLE PROTECTION HOSE**RUBBER CABLE PROTECTION
HOSE**

RUBBER



JABO PART#	SIZE	WORKING PSI 68F/104F
*	1/2"	75
*	5/8"	75
*	3/4"	75
*	1"	75
*	1-1/4"	75
*	1-1/2"	75
*	1-3/4"	75
*	2"	75
*	2-1/2"	75
*Non Stock - Call Jabo Supply		

**MSHA
Accepted****T966AA Series
CABLE PROTECTION
HOSE****General Applications:**

Cable protection in underground mining operations. Also suitable for light duty air and water applications up to 75 psi working pressures.

Service Temperature Range:

-22°F (-30°C) to +176 °F (+80°C)

Branding:

ALFAGOMMA ITALY 966 CABLE COVER MSHA
IC-152/23 5 bar (75 psi) (in orange letters)

MSHA Accepted - Hose is accepted as having met the Interim Fire Criteria Acceptance of Products Taken Into Underground Mines per MSHA IC-152/23.

CABLE GUARD-RUBBER
PROTECTION**Nominal Specifications**

Series Number	ID		OD		Max Rec. WP (psi)	Min. Bend Radius at 68°F (in)	Std. Length Coils (ft)	Weight (lbs/ft)
	(in)	(mm)	(in)	(mm)				
T966AA050	1/2	13	0.83	21	75	4	100	0.17
T966AA062	5/8	16	0.94	26	75	5	100	0.19
T966AA075	3/4	19	1.14	29	75	6	100	0.28
T966AA100	1	25	1.38	35	75	8	100	0.35
T966AA125	1 1/4	32	1.65	42	75	10	100	0.43
T966AA150	1 1/2	38	1.89	48	75	15	100	0.50
T966AA175	1 3/4	45	2.17	55	75	18	100	0.58
T966AA200	2	51	2.40	61	75	20	100	0.65
T966AA250	2 1/2	63	2.87	73	75	25	100	0.82

